

## LED Fluorescent Tube-T8

**Features:**



1. Low Power consumption. 2. Only with High efficiency. 3. Low current requirement. 4. Long Life span. 5. Energy Conservation and environmental friendly. 6. This product don't contained restriction substance, compliance ROHS standard.

**Applications:**

1. Streetlamp. 2. Office building. 3. any type of store. 4. Advertising Moving Sign. 5. (Highway) tunnel.

procoudition: not damaged on purpose by people

1. The damage caused in delivery after shipment is in the charge of our company. (from the result of our package) - 2. guarantee to exchange in the first 2 years and repair in the third year;

model type	Main Parameter	
<b>YHX-T8-120-6W(SMD3528)</b> 	Material: PC/aluminium	Condition Temperature: -20 ~ +50°C
	LED Qty: 120PCS	Work Humidity: >95%
	Light Efficiency :90LM/W	Colour rendering index: 84Ra
	Imput Voltage: AC85-265V	Power Factor: ≥0.85
	Output voltage :DC9.8V-37V	Input Current :27.5mA
	Lumens Flux(LM): 400-576	Equal to Conventional Lamp: 20W
	Work Frequency: 50-60HZ	Luminance :250
	Life time: 30000H	Certification: CE&ROHs
	Color Temperature: 3500-6800K	Spec.: length 595mm diameter 30mm
<b>YHX-T8-288-18W(SMD3528)</b> 	Material: PC/aluminium	Condition Temperature: -20 ~ +50°C
	LED Qty: 288PCS	Work Humidity: >95%
	Light Efficiency :90LM/W	Colour rendering index: 84Ra
	Imput Voltage: AC85-265V	Power Factor: ≥0.85
	Output voltage :DC9.8V-37V	Input Current :81.5mA
	Lumens Flux(LM): 1200-1728	Equal to Conventional Lamp: 45W
	Work Frequency: 50-60HZ	Luminance :590
	Life time: 30000H	Certification: CE&ROHs
	Color Temperature: 3500-6800K	Spec.: length 1196mm diameter 30mm



## LED Fluorescent Tube-T8

### Features:



1. Low Power consumption. 2. Only with High efficiency. 3. Low current requirement. 4. Long Life span. 5. Energy Conservation and environmental friendly. 6. This product don't contained restriction substance, compliance ROHS standard.

### Applications:

1. Streetlamp. 2. Office building. 3. any type of store. 4. Advertising Moving Sign. 5. (Highway) tunnel.

procoudition: not damaged on purpose by people

1. The damage caused in delivery after shipment is in the charge of our company. (from the result of our package) - 2. guarantee to exchange in the first 2 years and repair in the third year;

model type	Main Parameter	
<b>YHX-T8-120-6W</b>  	Material: PC/aluminium	Condition Temperature: -20 ~ +50°C
	LED Qty: 120PCS (5mm led la	Work Humidity: >95%
	Light Efficiency :90LM/W	Colour rendering index: 84Ra
	Imput Voltage: AC85-265V	Power Factor: ≥0.85
	Output voltage :DC9.8V-37V	Input Current :27.5mA
	Lumens Flux(LM): 400-576	Equal to Conventional Lamp: 20W
	Work Frequency: 50-60HZ	Luminance :250
	Life time: 30000H	Certification: CE&ROHs
	Color Temperature: 3500-6800K	Spec.: length 595mm diameter 30mm
<b>YHX-T8-288-18W</b>  	Material: PC/aluminium	Condition Temperature: -20 ~ +50°C
	LED Qty: 288PCS(5mm led lam	Work Humidity: >95%
	Light Efficiency :90LM/W	Colour rendering index: 84Ra
	Imput Voltage: AC85-265V	Power Factor: ≥0.85
	Output voltage :DC9.8V-37V	Input Current :81.5mA
	Lumens Flux(LM): 1200-1728	Equal to Conventional Lamp: 45W
	Work Frequency: 50-60HZ	Luminance :590
	Life time: 30000H	Certification: CE&ROHs
	Color Temperature: 3500-6800K	Spec.: length 1196mm diameter 30mm